	Model :	6M11G2D0/6	Date :	09/12/20
	PowerKit Engine Scope Of Supply		Page :	1 / 3

Basic data

Engine model	6M11G2D0/6
Configuration N°	TBA
N° of Cylinders / Valves	6 / 12
Cylinders arrangement	In line
Displacement (L)	6.75
Thermodynamic Cycle	Diesel 4 stroke
Cooling System	Liquid (water + 50% antifreeze)
Injection System	Direct
Fuel System	Mechanical Pump
Aspiration	Turbocharged and Aftercooled
Flywheel housing	SAE 1
Flywheel	14"
Max. working ambient temperature	See derating curves
Max. working altitude	See derating curves
Front engine mounting brackets	Supplied mounted
Rear engine mounting brackets	Supplied mounted

Lubrication system


Lubricating oil low pressure alarm sensor (LOP)	Supplied
Lowest oil pressure alarm (shutdown) (Bar)	1
Lubricating oil pressure sensor for gauge supplied	0-10 Bar Vdo match scale
Lubricating oil temperature sensor for gauge	Not supplied
Replaceable oil filter(s)	Supplied
Oil and oil filter(s) element(s) change interval	Every 500 running hours
Oil dipstick mounted	Supplied
Manual oil drain pump	Not supplied
Oil pre-lubricating electric pump	Not supplied and not necessary

Intercooling system

Intercooler type	Air to Air
------------------	-------	------------

Air intake system

Air filter(s) with connection pipe(s) with replaceable cartridges supplied	Mounted
Visual indicator for dirty filter	Supplied
Electrical air heater	Optional

	Model :	6M11G2D0/6	Date :	09/12/20
	PowerKit Engine Scope Of Supply		Page :	2 / 3

Cooling system with standard radiator

Execution with radiator

System designed for ambient temperature up to (°C) ¹	50
Radiator with connecting parts supplied	Mounted
Radiator type	Mechanical
Fan type	Belt driven pusher
Front radiator guard	Supplied
Fan guard	Supplied
Low water level sensor	Not supplied
Coolant capacity of radiator and pipes (L)	12

Execution without radiator

Radiator	Not supplied
Connection pipes between engine and radiator	Not supplied
Flexible pipes for connection	Not supplied
Fan	Not supplied
Protection guards	Not supplied


Common data for both the above mentioned versions

Coolant capacity of the engine (L)	8
Coolant high temperature alarm sensor (HWT)	Supplied
Coolant alarm (shutdown) temperature (°C)	105
Coolant temperature sensor for gauge supplied	40-120°C Vdo match scale

Exhaust system

Dry type exhaust pipe with heat shield	Supplied
Flange installed on the exit of the exhaust system.....	Supplied
Counter-flange with gasket and bolts for exhaust pipe connection.....	Supplied
Exhaust expansion joint with flanges	Optional
Silencer	Not supplied

¹ The indicated value is based on an AOT value of 50°C for an engine tested at 100% of the PRP Power, in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, without air recirculation, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present.

	Model :	6M11G2D0/6	Date :	09/12/20
	PowerKit Engine Scope Of Supply		Page :	3 / 3

Fuel system

Governor Electronic
Governor steady state speed stability at constant load (ISO 8528-5 Class G3) ≤ +/- 0.5 %
Fuel filter mounted type Fine double type
Primary fuel filter / water separator Not supplied
Fuel filter(s) element(s) change interval Every 500 running hours ¹
Fuel priming pump type Mechanical
Fuel cut off electrical valve Not supplied

¹ The indicated change interval running hours is the maximum period when using good quality fuel, (EN 590 standard); this is reduced if the fuel is low quality fuel, if the fuel is contaminated, if the fuel has presence of water.

Electrical system

Electrical system voltage (negative to ground) (Vdc) 24
Starter power (kW) 6
Battery charger current (A) 80
Engine electrical wiring Not supplied

Painting

“Moteurs-Baudouin” Blue for the diesel engine
Standard supplier for radiator, alternator battery charger, pipes and air filter(s)

Testing

Standard factory test not witnessed
Test report available only upon request

Documentation

Operation & Maintenance Manual in English language Supplied in soft copy

Packaging

Wooden pallet + plastic cover

Tools

Standard tool box Optional

Spare parts

One set of spare parts for first maintenance interval : oil + fuel filters + V-belts Optional

DPK-SOS-EN-6M11-2002-20-12-09_6M11G2D0-6_StdRad Moteurs Baudouin reserve the right to modify these specifications, without notice. Document not contractual.