	Model : <b>6M16V2D0</b>	Date : 17/02/22
	<b>PowerKit VS Variable Speed Engine Datasheet</b>	Page : 1 / 4


## Ratings

Maximum power at maximum speed (kWm) ..... **255**  
Maximum power at maximum speed (HP) ..... **346**

Speed - Rpm	1500	1600	1700	1800	1900	2000	2100	2200	
<b>Net Engine Industrial Continuous Power at the flywheel</b>									
Power	kWm	180	191	195	201	204	205	203	203
	HP	244.8	259.8	265.2	273.4	277.4	278.8	276.1	276.1
<b>Specific fuel consumption at 100% of engine power</b>									
gr/kWh	192.3	193.7	195.9	197.9	201.6	208.4	215.3	221.1	
Fuel consumption tolerance : +/- 5 %									

## Basic data

Engine model .....6M16V2D0  
N° of Cylinders / Valves .....6 / 12  
Cylinders arrangement ..... In line  
Bore x Stroke (mm) .....126 x 130  
Displacement (L) .....9.726  
Thermodynamic Cycle ..... Diesel 4 stroke  
Cooling System .....Liquid (water + 50% antifreeze)  
Injection System ..... Direct  
Fuel System ..... Mechanical Pump  
Aspiration ..... Turbocharged and Aftercooled  
Compression ratio .....17 : 1  
Flywheel housing ..... SAE 1  
Flywheel ..... 14"  
N° of teeth on flywheel ring gear .....136  
Inertia of flywheel (kg•m<sup>2</sup>) .....1.84  
Inertia of crankshaft (kg•m<sup>2</sup>) .....0.39  
Emission standard .....N/A  
Overall Dimensions with radiator (Length x Width x Height) (mm) ..... 1983 × 1033 × 1264  
Engine dry weight without radiator and without radiator pipes (kg) .....1020  
Engine dry weight with radiator and radiator pipes (kg) .....1122  
Engine wet weight with radiator (includes oil, coolant) (kg) .....1193

	Model : <b>6M16V2D0</b>	Date : 17/02/22
	<b>PowerKit VS Variable Speed Engine Datasheet</b>	

### Air intake system

Air intake temperature rise (°C) .....	≤ 15
Air intake restriction clean filter (mBar) .....	≤ 35
Air intake restriction dirty filter (mBar) .....	≤ 70
Recommended air flow at 1800 Rpm at max Industrial Continuous Power (m <sup>3</sup> /min) .....	19.8
Min. diameter of intake pipe (mm) .....	100

### Aftercooling system

Aftercooler system type .....	Air to Air
Aftercooler heat dissipating capacity at 1800 Rpm at max Industrial Continuous Power (kJ/s) .....	68.4
Max. intake temperature @ 25°C ambient temperature (°C) .....	55
Max. difference between intake temperature and ambient temperature (°C) .....	≤ 30
Max. intake pressure drop of aftercooler (mBar) .....	120

### Lubrication system


Oil capacity Low / High (L) .....	22 / 26
Oil pressure in normal condition idle speed (Bar) .....	1.3 - 2.8
Oil pressure in normal condition at 1800 Rpm at max Industrial Continuous Power (Bar) .....	3.5 - 5.8
Lowest oil pressure alarm (shutdown) (Bar) .....	1
Max. oil temperature (°C) .....	105
Oil flow (L/min) .....	167
Oil fuel consumption ratio based on engine fuel consumption data .....	≤ 0.2 %
Total system capacity (including filters) (L) .....	30

### Heat balance test data (with ambient temperature 28 °C)

Total heat dissipation at maximum speed at maximum power (kJ/s) .....	348.8
---	-------

### Exhaust system

Max. exhaust back pressure (mBar) .....	75
Max. exhaust temperature before turbocharger (°C) .....	≤ 700
Max. exhaust temperature after turbocharger (°C) .....	≤ 550
Exhaust flow at 1800 Rpm at max Industrial Continuous Power (m <sup>3</sup> /min) .....	50.3
Min. diameter of exhaust pipe (mm) .....	100
Max. bending moment of exhaust gas exit flange (Nm) .....	10

	Model : <b>6M16V2D0</b>	Date : 17/02/22
	<b>PowerKit VS Variable Speed Engine Datasheet</b>	

## Cooling system with standard radiator

System designed for ambient temperature up to (°C) <sup>1</sup> .....	50
Radiator type .....	Mechanical
Fan type .....	Belt driven pusher
Min. inside diameter of coolant outlet pipe (mm) .....	45
Coolant capacity of radiator and pipes (L) .....	20
Coolant alarm (shutdown) temperature (°C) .....	105
Thermostat opening temperature / full open temperature (°C) .....	71 / 82
Min. pressure in cooling system (Bar) .....	0.5
Coolant capacity of the engine (L) .....	22
Cooling fan airflow at 1800 Rpm at max Industrial Continuous Power (m <sup>3</sup> /min) .....	481.2
Max additional restriction - Duct allowance (Pa) .....	50
Fan absorbed power at 1800 Rpm (kW) .....	17.9

## Fuel system

Governor .....	Mechanical
Fuel cut off stopping system .....	Energized to run type
Max. restriction at fuel pump inlet (Bar) .....	0.18
Max. fuel return restriction (Bar) .....	0.22
Max. fuel inlet temperature (°C) .....	50
Fuel supply flow at 1800 Rpm at max Industrial Continuous Power (L/hr) .....	57
Min. pressure of fuel pump (Bar) .....	0.35
Min. diameter of inlet pipe (mm) .....	12
Min. diameter of return pipe (mm) .....	12

## Electrical system

Electrical system voltage (negative to ground) (Vdc) .....	24
Starter power (kW) .....	8.5
Battery charger current (A) .....	55
Battery charger absorbed power (kW) .....	1.6
Max. electric resistance of starting circuit (Ω) .....	0.004
Min. sectional area of wire (mm <sup>2</sup> ) .....	70
Min. cold start temperature without auxiliary starting device (°C) .....	- 10

<sup>1</sup> The indicated value is based on an AOT value of 50°C for an engine tested at 1800 Rpm at max Industrial Continuous Power, in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, without air recirculation, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present.

	Model : <b>6M16V2D0</b>	Date : 17/02/22
	<b>PowerKit VS Variable Speed Engine Datasheet</b>	

## Noise

Diesel engine noise (Acoustic power level) (dB(A)) .....	117
Noise - upper side (dB(A)) .....	100.1
Noise - right side (view from flywheel) (dB(A)) .....	102.6
Noise - left side (view from flywheel) (dB(A)) .....	102.5
Noise – front (radiator) side (dB(A)) .....	101.3
Noise – rear (flywheel) side (dB(A)) .....	100.5

### Notes :

- a) Noise test made at 1800 Rpm at 100% of the power, 1 mt. distance, on engine without radiator, without cooling fan and without silencer.
- b) Noise test refers to GB/T 1859 norm : Reciprocating internal combustion engines. "Measurement of emitted airborne noise. Engineering method and survey method".

## Ratings definitions

### Industrial Continuous Power

This power rating is for applications that operate with constant load and speed except for short periods during startup or shutdown. This rating conforms to ISO 3046 Continuous Power.

- 1) All ratings are based on operating conditions under ISO 3046, DIN6271. Performance tolerance of  $\pm 5\%$ .
- 2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Max power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.